

Rifle Reloading data

Cartridge

Cartridge .270 Winchester
Test barrel 620 mm (24 $\frac{3}{8}$ "), 1 in 10" twist
Primers Large Rifle
Cases Remington, trim-to length 64,30 mm (2.531")



Bullet specifications

Your search returned **44** different loads:

Bullet				Powder	Load			
gr			inch		gr	fps		
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
100	Speer	Spitzer	3.150	N150	44.5	52.8	2945	3273
100	Speer	Spitzer	3.150	N160	58.6	65.8	3127	3468
100	Speer	Spitzer	3.150	N165	61.7	69.9	3170	3509
115	Sierra	MatchKing	3.287	N150	39.5	45.4	2733	3031
115	Sierra	MatchKing	3.287	N550	44.3	49.1	2858	3130
115	Sierra	MatchKing	3.287	N160	46.0	54.6	2769	3143
130	Remington	SP	3.228	N160	51.5	58.0	2779	3083
130	Remington	SP	3.228	N560	56.2	61.3	2873	3132
130	Rhino	Solid Shank	3.268	N555	50.9	54.5	2864	3051
130	Rhino	Solid Shank	3.268	N160	49.4	54.3	2733	2969
130	Rhino	Solid Shank	3.268	N165	55.6	59.1	2864	3058
130	Rhino	Solid Shank	3.268	N560	52.5	56.6	2795	3031
130	Speer	SPBT	3.268	N165	54.6	62.0	2787	3089
130	Swift	Scirocco II	3.331	N555	50.3	54.5	2867	3084
130	Swift	Scirocco II	3.331	N160	45.5	54.2	2684	2992
130	Swift	Scirocco II	3.331	N165	54.0	60.2	2874	3120
130	Swift	Scirocco II	3.331	N560	54.0	59.0	2831	3104
130	Swift	Scirocco II	3.331	N565	55.6	60.5	2831	3068
135	Sierra	HPBT	3.268	N160	44.8	56.5	2697	3048
135	Sierra	HPBT	3.268	N165	56.3	60.2	2769	3041
135	Sierra	HPBT	3.268	N560	55.9	60.3	2874	3140
140	Barnes	TSX	3.209	N550	37.7	46.5	2418	2822
140	Barnes	TSX	3.209	N165	44.8	52.8	2533	2828
140	Barnes	TSX	3.209	N560	48.1	53.7	2618	2894
140	Rhino	Solid Shank	3.268	N160	47.1	52.8	2598	2864
140	Rhino	Solid Shank	3.268	N165	52.5	56.8	2700	2930

Bullet				Powder	Load			
gr			inch		gr		fps	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
140	Rhino	Solid Shank	3.268	N560	50.2	54.9	2667	2930
140	Swift	A-Frame	3.228	N550	40.6	47.5	2487	2818
140	Swift	A-Frame	3.228	N165	47.1	55.4	2592	2844
140	Swift	A-Frame	3.228	N560	48.1	55.6	2589	2913
150	Barnes	TSX	3.228	N550	37.7	45.2	2336	2694
150	Barnes	TSX	3.228	N165	41.8	50.5	2339	2687
150	Barnes	TSX	3.228	N560	44.8	51.9	2448	2779
150	Nosler	Ballistic Tip	3.287	N160	45.1	52.3	2395	2762
150	Nosler	Ballistic Tip	3.287	N165	47.8	57.7	2408	2854
150	Nosler	Ballistic Tip	3.287	N560	48.3	56.5	2434	2854
150	Swift	A-Frame	3.331	N555	44.8	50.3	2579	2812
150	Swift	A-Frame	3.331	N160	42.4	47.8	2444	2680
150	Swift	A-Frame	3.331	N165	47.8	55.4	2579	2835
150	Swift	A-Frame	3.331	N560	49.4	55.4	2608	2887
150	Swift	A-Frame	3.331	N565	50.9	56.3	2628	2858
160	Nosler	Partition	3.331	N160	38.6	44.6	2293	2562
160	Nosler	Partition	3.331	N165	44.4	51.1	2411	2661
160	Nosler	Partition	3.331	N560	46.5	52.8	2444	2779