

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------	-------------	-------------	---------------------	----------------------	-------------------	--------------------	--------------------	--------------

45 AUTO (ACP)

Barrel: 5" | Twist: 1-16" | Primer: FED 150 | Bullet Diameter: 0.451"

Case: REM | Max Case Length: 0.898" | Trim Length: 0.893"

ACCURATE NITRO 100 NF

185	REM	GS	4.2	845	4.9	940	20,772	1.225
185 (P)	BERRY	SWC	3.9	861	4.6	937	20,196	1.198
185 (P)	BERRY	FP	4.3	891	5.0	978	20,714	1.197
185 (P)	BERRY	HBRN	4.5	877	5.3	977	20,647	1.270
200 (P)	BERRY	HP	3.8	790	4.5	893	20,914	1.205
200 (P)	BERRY	FP	3.9	813	4.5	901	20,569	1.205
200 (P)	BERRY	SWC	3.7	828	4.4	895	20,419	1.205
200 (P)	RAIN	FP	3.8	815	4.4	899	20,664	1.245
230	HDY	XTP	3.3	664	3.8	741	20,698	1.210
230 (P)	BERRY	RN	3.7	753	4.4	829	20,905	1.237
230 (P)	RAIN	HP	3.5	610	4.1	728	20,211	1.237
230 (L)	LC	RN	3.6	770	4.0	823	20,912	1.230

RAMSHOT COMPETITION

155 (L)	LC	SWC	4.5	950	5.0	1,056	19,200	1.232
180 (L)	LC	SWC	4.2	861	4.7	957	19,610	1.267
185	HDY	XTP	4.6	847	5.1	941	20,530	1.230
185	NOSLER	JHP	4.3	845	5.1	954	20,945	1.200
185	REM	GS	4.4	882	5.1	967	20,418	1.225
185 (P)	BERRY	SWC	4.2	848	4.9	952	20,425	1.198
185 (P)	BERRY	FP	4.4	866	5.2	980	20,418	1.197
185 (P)	BERRY	HBRN	4.6	872	5.4	977	20,708	1.270
200	HDY	FMJ CT	4.0	774	4.4	860	20,600	1.230
200	SIERRA	FPJ	4.0	782	4.7	881	20,728	1.155
200 (P)	BERRY	HP	4.0	810	4.7	902	20,487	1.205
200 (P)	BERRY	FP	4.2	813	4.9	915	20,932	1.205
200 (P)	BERRY	SWC	4.0	838	4.7	919	20,970	1.205
200 (P)	RAIN	FP	4.0	807	4.7	905	20,489	1.245
200 (P)	RAIN	RN	4.5	796	5.3	927	20,367	1.269
200 (L)	LC	SWC	3.9	806	4.3	896	20,040	1.267
230	HDY	XTP	3.3	672	3.9	746	20,741	1.210
230	REM	GS	3.6	716	4.2	792	20,840	1.225
230	SIERRA	FMJ	3.8	691	4.5	793	20,657	1.270
230 (P)	RAIN	HP	3.7	642	4.4	747	20,654	1.237
230 (L)	LC	SWC	3.6	725	4.0	805	19,230	1.267

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
---------------------------	-------------	-------------	------------------------	-------------------------	----------------------	-----------------------	-----------------------	-----------------

RAMSHOT ZIP

140	SF	RHFP	6.2	1,022	6.9	1,136	20,110	1.210
155	SF	RHFP	5.2	901	5.8	1,001	19,030	1.210
155 (L)	LC	SWC	6.5	1,060	7.2	1,178	20,940	1.232
180 (L)	LC	SWC	6.0	957	6.7	1,063	20,510	1.267
185	HDY	XTP	6.6	946	7.3	1,051	19,590	1.230
185	REM	GS	6.2	948	7.3	1,078	20,637	1.225
185	BARNES	TAC-XP	4.8	803	5.3	892	20,035	1.235
185 (P)	BERRY	SWC	5.8	884	6.8	1,041	20,148	1.198
185 (P)	BERRY	FP	6.0	929	7.1	1,066	20,186	1.197
185 (P)	BERRY	HBRN	6.5	944	7.6	1,087	20,269	1.270
200	HDY	FMJ CT	5.8	879	6.4	977	20,650	1.230
200 (P)	BERRY	HP	5.7	863	6.7	1,012	20,555	1.205
200 (P)	BERRY	FP	6.0	904	7.1	1,039	20,765	1.205
200 (P)	BERRY	SWC	5.5	908	6.5	1,013	20,711	1.205
200 (P)	RAIN	FP	5.5	863	6.5	1,010	20,633	1.245
200 (P)	RAIN	RN	6.0	911	7.1	1,036	20,779	1.269
200 (L)	LC	SWC	5.6	897	6.2	997	20,290	1.267
230	HDY	XTP	4.5	703	5.3	816	20,718	1.210
230	REM	GS	4.8	773	5.7	873	20,456	1.225
230	SIERRA	FMJ	5.6	814	6.2	904	20,680	1.250
230 (P)	BERRY	RN	5.1	778	6.0	899	20,547	1.237
230 (P)	RAIN	HP	5.0	748	5.9	862	20,483	1.237
230 (L)	LC	SWC	5.2	824	5.8	915	20,318	1.267

ACCURATE SOLO 1000

155 (L)	LC	SWC	5.9	1,029	6.5	1,170	19,100	1.240
170 (L)	MCB	SWC	5.3	931	5.9	1,059	17,800	1.130
185	REM	GS	5.2	883	6.1	1,008	20,596	1.225
185	SIERRA	JHP	5.5	862	6.1	980	19,400	1.210
185 (P)	BERRY	SWC	5.0	863	5.9	998	20,650	1.198
185 (P)	BERRY	FP	5.1	917	6.0	1,021	20,841	1.197
185 (P)	BERRY	HBRN	5.5	903	6.5	1,021	20,852	1.270
200	HDY	XTP	5.2	804	5.8	914	18,800	1.225
200 (P)	BERRY	HP	4.8	811	5.6	947	20,747	1.205
200 (P)	BERRY	FP	4.8	830	5.7	943	20,327	1.205
200 (P)	BERRY	SWC	4.8	824	5.6	950	20,047	1.205
200 (P)	RAIN	FP	4.8	868	5.7	960	20,498	1.245
200 (P)	RAIN	RN	5.3	863	6.2	974	20,687	1.269
200 (L)	LC	SWC	4.8	838	5.3	952	18,300	1.190

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
---------------------------	-------------	-------------	------------------------	-------------------------	----------------------	-----------------------	-----------------------	-----------------

ACCURATE SOLO 1000 *(continued)*

230	HDY	XTP	4.0	695	4.7	789	20,585	1.210
230	NOSLER	FMJ	4.9	746	5.5	848	18,900	1.250
230	REM	GS	4.3	753	5.0	831	20,365	1.225
230 (P)	BERRY	RN	4.4	760	5.1	846	20,655	1.237
230 (P)	RAIN	HP	4.3	705	5.1	802	20,224	1.237
230 (L)	LC	RN	4.6	790	5.1	898	18,300	1.230

ACCURATE NO. 2

140	SF	RHFP	5.2	978	5.8	1,087	20,480	1.210
155	SF	RHFP	4.6	882	5.1	980	20,420	1.210
155 (L)	LC	SWC	5.8	1,004	6.8	1,138	20,600	1.225
160	BARNES	TAC-XP	4.7	923	5.5	1,016	20,741	1.256
170 (L)	MCB	SWC	5.9	950	6.5	1,079	19,400	1.130
185	NOSLER	JHP	5.7	948	6.7	1,106	20,750	1.210
185	BARNES	TAC-XP	4.5	770	5.0	856	20,265	1.235
185	REM	GS	5.5	871	6.4	1,018	20,875	1.225
185 (P)	BERRY	SWC	5.4	913	6.4	1,022	20,712	1.195
185 (P)	BERRY	FP	5.4	892	6.3	1,014	20,867	1.195
185 (P)	BERRY	HBRN	6.0	880	7.0	1,014	20,219	1.270
185 (P)	RAIN	HP	5.6	885	6.6	1,011	20,575	1.220
185 (L)	MCB	SWC	5.6	895	6.2	1,000	18,500	1.210
200	HDY	XTP	5.1	855	5.8	970	19,900	1.225
200 (P)	BERRY	HP	5.3	846	6.3	962	20,642	1.205
200 (P)	BERRY	FP	5.4	844	6.3	958	20,213	1.205
200 (P)	BERRY	SWC	5.1	845	6.0	958	20,692	1.212
200 (P)	RAIN	FP	5.0	821	5.9	932	20,074	1.245
200 (L)	LC	SWC	5.2	826	5.8	939	17,400	1.190
230	HDY	XTP	4.3	697	5.1	799	20,958	1.210
230	REM	GS	4.5	742	5.3	853	20,473	1.225
230	SIERRA	FMJ	4.6	769	5.4	881	20,800	1.250
230 (P)	BERRY	RN	4.6	730	5.4	842	20,412	1.237
230 (P)	RAIN	HP	4.6	721	5.4	831	20,745	1.237
230 (L)	LC	RN	5.0	766	5.6	870	17,200	1.230
250 (P)	BERRY	FP	3.9	645	4.6	749	20,194	1.200
250 (P)	RAIN	FP	4.1	680	4.8	780	20,606	1.200

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

RAMSHOT SILHOUETTE

120	LHG	XP	9.8	1,181	10.9	1,351	20,946	1.232
140	SF	RHFP	8.0	1,060	8.9	1,178	19,390	1.210
155	SF	RHFP	7.1	990	7.9	1,100	20,740	1.210
155 (L)	LC	SWC	7.5	1,058	8.9	1,230	20,742	1.225
160	BARNES	TAC-XP	6.7	961	7.9	1,125	20,443	1.256
170	LHG	CF	7.0	919	7.7	1,040	20,682	1.235
180 (L)	LC	SWC	8.0	991	8.9	1,101	18,250	1.267
185	HDY	XTP	8.9	1,037	9.9	1,152	20,900	1.230
185	REM	GS	7.6	972	8.9	1,118	20,746	1.225
185	BARNES	TAC-XP	6.2	870	7.3	1,017	20,366	1.256
185 (P)	BERRY	SWC	7.5	949	8.9	1,116	20,841	1.195
185 (P)	BERRY	FP	7.7	930	9.1	1,095	20,590	1.195
185 (P)	BERRY	HBRN	8.3	929	9.7	1,123	20,689	1.270
185 (P)	RAIN	HP	7.8	926	9.1	1,092	20,662	1.220
200	LHG	XP	6.5	789	7.2	900	20,697	1.235
200	HDY	FMJ CT	7.6	937	8.4	1,041	20,230	1.230
200 (P)	BERRY	HP	7.2	885	8.5	1,034	20,315	1.205
200 (P)	BERRY	FP	7.4	878	8.7	1,034	20,305	1.205
200 (P)	BERRY	SWC	6.9	886	8.2	1,032	20,197	1.212
200 (P)	RAIN	FP	7.0	906	8.2	1,039	20,589	1.245
200 (P)	RAIN	RN	7.5	895	8.8	1,046	20,607	1.269
200 (L)	LC	SWC	7.6	964	8.4	1,071	20,349	1.267
230	HDY	XTP	6.2	785	7.3	916	20,867	1.210
230	REM	GS	6.5	838	7.6	966	20,532	1.225
230	SIERRA	FMJ	7.3	868	8.1	964	19,740	1.250
230 (P)	BERRY	RN	6.6	811	7.8	957	20,943	1.237
230 (P)	RAIN	HP	6.4	808	7.5	943	20,498	1.237
250 (P)	BERRY	FP	5.6	741	6.6	866	20,398	1.200
250 (P)	RAIN	FP	5.8	766	6.8	893	20,681	1.200

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
RAMSHOT TRUE BLUE								
120	LHG	XP	9.2	1,127	10.2	1,255	20,875	1.232
140	SF	RHFP	7.7	1,009	8.6	1,121	20,250	1.210
155	SF	RHFP	6.8	916	7.6	1,018	20,310	1.210
155 (L)	LC	SWC	8.4	1,049	9.3	1,165	20,030	1.232
160	BARNES	TAC-XP	6.8	948	7.9	1,081	20,397	1.256
170	LHG	CF	6.7	865	7.4	962	20,746	1.235
180 (L)	LC	SWC	7.7	947	8.5	1,052	19,510	1.267
185	HDY	XTP	8.5	980	9.4	1,089	20,780	1.230
185	REM	GS	7.6	947	9.0	1,087	20,822	1.225
185	BARNES	TAC-XP	5.9	857	7.0	965	20,188	1.256
185 (P)	BERRY	SWC	7.5	942	8.8	1,086	20,958	1.195
185 (P)	BERRY	FP	7.7	936	9.1	1,091	20,906	1.195
185 (P)	BERRY	HBRN	8.1	954	9.6	1,091	20,499	1.270
185 (P)	RAIN	HP	7.6	924	9.0	1,068	20,399	1.220
200	LHG	XP	6.3	760	7.0	846	20,628	1.235
200	HDY	FMJ CT	7.2	866	8.0	962	19,490	1.230
200 (P)	BERRY	HP	7.4	893	8.7	1,038	20,815	1.205
200 (P)	BERRY	FP	7.7	919	9.1	1,065	20,771	1.205
200 (P)	BERRY	SWC	7.0	884	8.2	1,009	20,444	1.212
200 (P)	RAIN	FP	7.0	876	8.2	1,010	20,447	1.245
200 (P)	RAIN	RN	7.6	891	8.9	1,036	20,733	1.269
230	HDY	XTP	5.8	722	6.8	851	20,916	1.210
230	REM	GS	6.2	810	7.3	909	20,128	1.225
230	SIERRA	FMJ	6.8	800	7.6	889	19,680	1.250
230 (P)	BERRY	RN	6.6	820	7.8	933	20,553	1.237
230 (P)	RAIN	HP	6.4	807	7.6	925	20,804	1.237
230 (L)	LC	SWC	6.7	822	7.4	913	19,450	1.267
250 (P)	BERRY	FP	5.7	731	6.7	839	20,899	1.200
250 (P)	RAIN	FP	5.8	739	6.8	854	20,863	1.212

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
<u>ACCURATE NO. 5</u>								
120	LHG	XP	10.3	1,135	11.5	1,283	20,959	1.232
140	SF	RHFP	8.7	1,044	9.7	1,160	20,350	1.210
155	SF	RHFP	7.3	923	8.1	1,025	19,430	1.210
155 (L)	LC	SWC	9.0	1,046	10.0	1,189	18,500	1.240
160	BARNES	TAC-XP	7.3	946	8.5	1,086	20,349	1.256
170	LHG	CF	7.5	892	8.3	990	20,864	1.235
170 (L)	MCB	SWC	8.1	945	9.0	1,074	17,800	1.130
185	HDY	XTP	9.2	970	10.2	1,102	19,900	1.210
185	NOSLER	JHP	8.2	929	9.7	1,071	20,999	1.200
185	REM	GS	8.1	929	9.5	1,088	20,490	1.225
185	BARNES	TAC-XP	6.5	813	7.2	903	20,375	1.235
185 (P)	BERRY	SWC	8.0	926	9.4	1,080	20,372	1.195
185 (P)	BERRY	FP	8.2	924	9.7	1,079	20,391	1.195
185 (P)	BERRY	HBRN	8.8	916	10.3	1,088	20,416	1.270
185 (P)	RAIN	HP	8.1	940	9.5	1,080	20,677	1.220
185 (L)	MCB	SWC	8.0	925	8.9	1,050	18,500	1.230
200	LHG	XP	7.0	769	7.8	869	20,893	1.235
200	SIERRA	FPJ	7.6	854	8.9	996	20,493	1.155
200 (P)	BERRY	HP	7.7	892	9.1	1,022	20,058	1.205
200 (P)	BERRY	FP	7.9	870	9.3	1,024	20,559	1.205
200 (P)	BERRY	SWC	7.5	868	8.8	1,010	20,114	1.212
200 (P)	RAIN	FP	7.6	881	8.9	1,026	20,740	1.245
200 (P)	RAIN	RN	8.2	904	9.6	1,044	20,744	1.269
200 (L)	LC	SWC	7.8	902	8.7	1,025	19,400	1.190
230	HDY	XTP	6.6	751	7.7	869	20,998	1.210
230	NOSLER	FMJ	7.8	816	8.7	927	19,300	1.250
230	REM	GS	7.0	810	8.2	935	20,694	1.225
230	SIERRA	FMJ	7.4	814	8.7	939	20,921	1.270
230 (P)	BERRY	RN	7.1	784	8.3	929	20,142	1.237
230 (P)	RAIN	HP	7.0	807	8.2	934	20,814	1.237
230 (L)	MCB	RN BB	7.7	852	8.5	968	19,800	1.230
250 (P)	BERRY	FP	6.0	718	7.1	838	20,489	1.200
250 (P)	RAIN	FP	6.2	737	7.3	864	20,948	1.212

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

ACCURATE NO. 7

155 (L)	LC	SWC	12.0	1,076	13.3	1,223	20,200	1.240
160	BARNES	TAC-XP	8.8	934	10.4	1,082	20,740	1.256
170 (L)	MCB	SWC	11.3	1,031	12.5	1,172	20,800	1.130
185	SIERRA	JHP	11.7	962	13.0	1,093	18,000	1.210
185	REM	GS	10.1	929	11.9	1,095	20,674	1.225
185	BARNES	TAC-XP	8.1	827	9.0	919	20,155	1.235
185 (P)	BERRY	SWC	9.7	904	11.4	1,073	20,489	1.195
185 (P)	BERRY	FP	10.1	909	11.9	1,096	20,777	1.195
185 (P)	BERRY	HBRN	10.8	920	12.7	1,109	20,875	1.270
185 (P)	RAIN	HP	10.0	915	11.7	1,092	20,902	1.220
200	HDY	XTP	10.8	912	12.0	1,036	19,200	1.225
200 (P)	BERRY	HP	9.4	868	11.0	1,031	20,499	1.205
200 (P)	BERRY	FP	9.9	887	11.6	1,054	20,488	1.205
200 (P)	RAIN	FP	9.2	862	10.8	1,021	20,674	1.245
200 (P)	RAIN	RN	9.9	873	11.6	1,045	20,500	1.269
200 (L)	LC	SWC	10.4	899	11.5	1,022	18,700	1.190
230	HDY	XTP	7.8	743	9.2	895	20,946	1.210
230	REM	GS	8.5	822	10.0	943	20,990	1.225
230 (P)	BERRY	RN	8.6	800	10.1	945	20,777	1.237
230 (P)	RAIN	HP	8.3	778	9.8	930	20,668	1.237
230 (L)	LC	RN	9.9	862	11.0	979	19,400	1.230
250 (P)	BERRY	FP	7.3	744	8.6	845	20,667	1.200
250 (P)	RAIN	FP	7.5	731	8.8	863	20,147	1.212

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

45 AUTO (ACP) +P

Barrel: 5" | Twist: 1-16" | Primer: FED 150 | Bullet Diameter: 0.451"
Case: REM | Max Case Length: 0.898" | Trim Length: 0.893"

ACCURATE NITRO 100 NE

185	REM	GS	4.9	928	5.2	968	22,320	1.225
185 (P)	BERRY	SWC	4.6	936	4.9	967	22,717	1.198
185 (P)	BERRY	FP	5.0	974	5.4	1,018	22,878	1.197
185 (P)	BERRY	HBRN	5.3	968	5.7	1,018	22,908	1.270
200 (P)	BERRY	FP	4.5	901	4.9	945	22,816	1.205
200 (P)	BERRY	HP	4.5	887	4.8	939	22,739	1.205
200 (P)	BERRY	SWC	4.4	898	4.6	922	22,316	1.205
200 (P)	RAIN	FP	4.4	900	4.7	929	22,553	1.245
230	HDY	XTP	3.8	739	4.1	783	22,970	1.210
230 (P)	BERRY	RN	4.4	832	4.6	859	22,903	1.237
230 (P)	RAIN	HP	4.1	730	4.3	781	22,958	1.237
230 (L)	LC	RN	4.0	823	4.2	848	22,943	1.230

RAMSHOT COMPETITION

185	NOSLER	JHP	5.1	961	5.4	1,000	22,793	1.200
185	REM	GS	5.1	968	5.5	1,014	22,764	1.225
185 (P)	BERRY	SWC	4.9	954	5.2	999	22,848	1.198
185 (P)	BERRY	FP	5.2	980	5.5	1,027	22,918	1.197
185 (P)	BERRY	HBRN	5.4	977	5.9	1,038	22,933	1.270
200 (P)	BERRY	HP	4.7	900	5.0	939	22,715	1.205
200 (P)	BERRY	FP	4.9	918	5.2	962	22,900	1.205
200 (P)	BERRY	SWC	4.7	920	5.0	956	22,771	1.205
200 (P)	RAIN	FP	4.7	905	4.9	940	22,417	1.245
230	HDY	XTP	3.9	749	4.2	781	22,910	1.210
230	REM	GS	4.2	795	4.4	822	22,994	1.225
230 (P)	RAIN	HP	4.4	750	4.6	788	22,594	1.237

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

RAMSHOT ZIP

185	REM	GS	7.3	1,081	7.6	1,119	22,503	1.225
185 (P)	BERRY	SWC	6.8	1,041	7.2	1,105	22,237	1.198
185 (P)	BERRY	FP	7.1	1,067	7.5	1,129	22,551	1.197
185 (P)	BERRY	HBRN	7.6	1,086	8.2	1,158	22,711	1.270
200 (P)	BERRY	HP	6.7	1,003	7.1	1,067	22,504	1.205
200 (P)	BERRY	FP	7.1	1,040	7.4	1,078	22,973	1.205
200 (P)	BERRY	SWC	6.5	1,012	6.9	1,057	22,965	1.205
200 (P)	RAIN	FP	6.5	1,007	6.7	1,048	22,256	1.245
200 (P)	RAIN	RN	7.1	1,037	7.5	1,082	22,739	1.269
230	HDY	XTP	5.3	814	5.7	862	22,810	1.210
230	REM	GS	5.7	876	6.0	912	22,932	1.225
230 (P)	BERRY	RN	6.0	893	6.3	936	22,718	1.237
230 (P)	RAIN	HP	5.9	867	6.2	907	22,656	1.237

ACCURATE SOLO 1000

185	REM	GS	6.1	1,018	6.5	1,064	22,933	1.225
185 (P)	BERRY	SWC	5.9	986	6.3	1,054	22,318	1.198
185 (P)	BERRY	FP	6.0	1,015	6.4	1,059	22,744	1.197
185 (P)	BERRY	HBRN	6.5	1,024	6.8	1,066	22,837	1.270
200 (P)	BERRY	FP	5.7	946	6.2	1,003	22,734	1.205
200 (P)	BERRY	SWC	5.6	943	6.1	1,017	22,661	1.205
200 (P)	RAIN	FP	5.7	963	6.1	1,002	22,799	1.245
200 (P)	RAIN	RN	6.2	975	6.6	1,015	22,102	1.269
230	HDY	XTP	4.7	787	5.0	827	22,770	1.210
230	REM	GS	5.0	834	5.4	868	22,940	1.225
230 (P)	BERRY	RN	5.1	842	5.4	879	22,694	1.237
230 (P)	RAIN	HP	5.1	800	5.5	848	22,859	1.237

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------	-------------	-------------	---------------------	----------------------	-------------------	--------------------	--------------------	--------------

ACCURATE NO.2

155 (L)	LC	SWC	6.8	1,136	7.1	1,174	22,295	1.225
160	BARNES	TAC-XP	5.5	1,010	5.9	1,056	22,790	1.256
185	REM	GS	6.4	1,014	6.7	1,066	22,481	1.225
185	BARNES	TAC-XP	5.1	926	5.5	973	22,626	1.256
185 (P)	BERRY	SWC	6.4	1,024	6.7	1,062	22,864	1.195
185 (P)	BERRY	FP	6.3	1,009	6.7	1,060	22,941	1.195
185 (P)	BERRY	HBRN	7.0	1,013	7.5	1,081	22,826	1.270
185 (P)	RAIN	HP	6.6	1,014	7.0	1,068	22,772	1.220
200 (P)	BERRY	HP	6.3	968	6.7	1,016	22,884	1.205
200 (P)	BERRY	FP	6.3	955	6.9	1,023	22,444	1.205
200 (P)	BERRY	SWC	6.0	956	6.3	995	22,840	1.212
230	HDY	XTP	5.1	797	5.3	833	22,776	1.210
230	REM	GS	5.3	851	5.7	899	22,892	1.225
230 (P)	BERRY	RN	5.4	835	5.8	891	22,904	1.237
230 (P)	RAIN	HP	5.4	829	5.7	868	22,815	1.237
250 (P)	BERRY	FP	4.6	752	4.9	805	22,952	1.200
250 (P)	RAIN	FP	4.8	777	5.1	819	22,904	1.200

RAMSHOT SILHOUETTE

120	LHG	XP	10.9	1,354	11.2	1,407	22,816	1.232
155 (L)	LC	SWC	8.9	1,231	9.3	1,279	22,949	1.225
160	BARNES	TAC-XP	7.9	1,123	8.3	1,181	22,309	1.256
170	LHG	CF	7.7	1,038	8.1	1,102	22,974	1.235
185	REM	GS	8.9	1,110	9.3	1,161	22,615	1.225
185	BARNES	TAC-XP	7.3	1,015	7.7	1,079	22,929	1.256
185 (P)	BERRY	SWC	8.9	1,122	9.3	1,169	22,960	1.195
185 (P)	BERRY	FP	9.1	1,099	9.7	1,171	22,882	1.195
185 (P)	BERRY	HBRN	9.7	1,123	10.2	1,193	22,833	1.270
185 (P)	RAIN	HP	9.1	1,089	9.7	1,161	22,711	1.220
200	LHG	XP	7.2	907	7.5	953	22,754	1.235
200 (P)	BERRY	HP	8.5	1,041	9.0	1,094	22,625	1.205
200 (P)	BERRY	FP	8.7	1,038	9.2	1,093	22,504	1.205
200 (P)	BERRY	SWC	8.2	1,034	8.8	1,109	22,362	1.212
200 (P)	RAIN	RN	8.8	1,046	9.5	1,124	22,816	1.269
230	HDY	XTP	7.3	917	7.7	963	22,968	1.210
230	REM	GS	7.6	960	8.1	1,014	22,760	1.225
230 (P)	BERRY	RN	7.8	957	8.2	1,009	22,835	1.237
230 (P)	RAIN	HP	7.5	951	7.9	999	22,826	1.237
250 (P)	BERRY	FP	6.6	873	7.0	918	22,954	1.200
250 (P)	RAIN	FP	6.8	894	7.1	929	22,898	1.200

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

RAMSHOT TRUE BLUE

120	LHG	XP	10.2	1,257	10.6	1,297	22,501	1.232
155 (L)	LC	SWC	8.9	1,171	9.5	1,235	22,944	1.225
160	BARNES	TAC-XP	7.9	1,078	8.4	1,135	22,969	1.256
170	LHG	CF	7.4	956	7.8	1,007	22,549	1.235
185	REM	GS	9.0	1,093	9.4	1,132	22,558	1.225
185	BARNES	TAC-XP	7.0	971	7.6	1,026	22,893	1.256
185 (P)	BERRY	SWC	8.8	1,091	9.2	1,132	22,948	1.195
185 (P)	BERRY	FP	9.1	1,087	9.7	1,165	22,979	1.195
185 (P)	BERRY	HBRN	9.6	1,098	10.2	1,157	22,834	1.270
185 (P)	RAIN	HP	9.0	1,063	9.7	1,147	22,590	1.220
200	LHG	XP	7.0	851	7.4	896	22,719	1.235
200 (P)	BERRY	HP	8.7	1,043	9.1	1,084	22,953	1.205
200 (P)	BERRY	FP	9.1	1,066	9.5	1,111	22,973	1.205
200 (P)	BERRY	SWC	8.2	1,008	8.9	1,082	22,962	1.212
200 (P)	RAIN	RN	8.9	1,036	9.6	1,109	22,786	1.269
230	HDY	XTP	6.8	847	7.1	883	22,638	1.210
230	REM	GS	7.3	910	7.8	952	22,287	1.225
230 (P)	BERRY	RN	7.8	931	8.4	988	22,606	1.237
230 (P)	RAIN	HP	7.6	933	8.0	975	22,956	1.237
250 (P)	RAIN	FP	6.8	859	7.2	900	22,952	1.212

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

ACCURATE NO.5

120	LHG	XP	11.5	1,280	11.9	1,342	22,553	1.232
155 (L)	LC	SWC	9.7	1,184	10.3	1,248	22,950	1.225
160	BARNES	TAC-XP	8.5	1,084	9.1	1,144	22,814	1.256
170	LHG	CF	8.3	982	8.7	1,033	22,760	1.235
185	NOSLER	JHP	9.7	1,078	10.0	1,108	22,601	1.200
185	REM	GS	9.5	1,084	10.1	1,152	22,694	1.225
185	BARNES	TAC-XP	7.5	959	7.9	1,016	22,789	1.256
185 (P)	BERRY	SWC	9.4	1,074	10.0	1,139	22,879	1.195
185 (P)	BERRY	FP	9.7	1,082	10.3	1,149	22,534	1.195
185 (P)	BERRY	HBRN	10.3	1,089	11.0	1,163	22,686	1.270
185 (P)	RAIN	HP	9.5	1,080	10.1	1,140	22,668	1.220
200	LHG	XP	7.8	868	8.2	921	22,774	1.235
200	SIERRA	FPJ	8.9	997	9.3	1,036	22,467	1.155
200 (P)	BERRY	HP	9.1	1,023	9.8	1,089	22,685	1.205
200 (P)	BERRY	FP	9.3	1,022	10.0	1,101	22,735	1.205
200 (P)	BERRY	SWC	8.8	1,009	9.5	1,081	22,623	1.212
200 (P)	RAIN	RN	9.6	1,047	10.2	1,108	22,940	1.269
230	HDY	XTP	7.7	868	8.1	909	22,850	1.210
230	REM	GS	8.2	927	8.6	971	22,384	1.225
230	SIERRA	FMJ	8.7	940	9.1	984	22,997	1.270
230 (P)	BERRY	RN	8.0	888	9.0	1,003	22,808	1.237
230 (P)	RAIN	HP	8.2	933	8.7	987	22,934	1.237
250 (P)	BERRY	FP	7.1	833	7.5	884	22,980	1.200
250 (P)	RAIN	FP	7.3	858	7.6	894	22,298	1.212

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (FPS)	Max Load (Grains)	Max Velocity (FPS)	Max Pressure (PSI)	COL (Inches)
------------------------------	----------------	----------------	---------------------------	----------------------------	-------------------------	--------------------------	--------------------------	-----------------

ACCURATE NO.7

160	BARNES	TAC-XP	10.4	1,080	10.8	1,122	22,371	1.256
185	REM	GS	11.9	1,101	12.4	1,148	22,874	1.225
185	BARNES	TAC-XP	9.1	960	9.5	1,004	22,617	1.256
185 (P)	BERRY	SWC	11.4	1,072	12.0	1,131	22,940	1.195
185 (P)	BERRY	FP	11.9	1,097	12.6	1,170	22,627	1.195
185 (P)	BERRY	HBRN	12.7	1,110	13.2	1,164	22,475	1.270
185 (P)	RAIN	HP	11.7	1,089	12.4	1,158	22,978	1.220
200 (P)	BERRY	HP	11.0	1,033	11.5	1,079	22,841	1.205
200 (P)	BERRY	FP	11.6	1,052	12.2	1,112	22,846	1.205
200 (P)	RAIN	RN	11.6	1,040	12.4	1,121	22,843	1.269
230	HDY	XTP	9.2	897	9.6	940	22,839	1.210
230	REM	GS	10.0	950	10.3	975	22,511	1.225
230 (P)	BERRY	RN	10.1	945	10.5	986	22,795	1.237
230 (P)	RAIN	HP	9.8	924	10.4	990	22,939	1.237
250 (P)	BERRY	FP	8.6	845	9.1	889	22,922	1.200
250 (P)	RAIN	FP	8.8	866	9.3	913	22,510	1.212